DELUXE SERIES

90 DAY LTD. COMMERCIAL WARRANTY

3 YEAR LTD. RESIDENTIAL WARRANTY

STRAIGHT-FORWARD POWER AND PERFORMANCE.

Clear snow without question or compromise. Easy maneuvering and control with Auto-Turn steering, standard on all Deluxe Sno-Thro's. With several engine choices and machine width's, there's a reason it's one of our best sellers. Now available with EFI, (electronic fuel injection) rest assured with less engine maintenance, increased fuel efficiency and easy one-pull starting. Our exclusive Dual-Belt Drive system provides unmatched power and increased belt life. While our Super High Output Impeller (SHO) technology will breeze through those heavy, wet storms with ease.

AUTO-TURN™ STEERING
Effortless, zero-degree turning radius.

DUAL-BELT DRIVE
Exclusive to Ariens, delivers maximum power through tough conditions, plus extended belt life.

AUGER
Our steel serrated 14" auger delivers exceptional performance through all types of snow conditions.

HEADLIGHT
Standard on all Deluxe series Sno-Thro's.

TIRES
16" directional tires provide improved mobility and agility.

ENGINE
Choose from three different types of Ariens AX engines.

*SUPER HIGH OUTPUT IMPELLER (SHO)
SHO impeller throws up to 82 tons of snow/hour.

*EZ-LAUNCH™ EFI ENGINE
Available EFI engine starts easier and uses less fuel with consistent power.

THROWING PERFORMANCE
Throw snow ranging from 3-55ft to allow for maximum precision.

* = AVAILABLE ON SELECT MODELS

PRODUCT SPECIFICATIONS

DESIGNATION	DELUXE 24	DELUXE 28	DELUXE 28 SHO	DELUXE 30	DELUXE 30 EFI
MODEL #	921045	921046	921048	921047	921049
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	254CC (12.5 FT/LBS)	254CC (12.5 FT/LBS)	306CC (15 FT/LBS)	306CC (15 FT/LBS)	306 CC EZ-LAUNCH EFI (15 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL
CLEARING WIDTH	24 IN (60.1 CM)	28 IN (71.2 CM)	28 IN (71.2 CM)	30 IN (76.2 CM)	30 IN (76.2 CM)
HOUSING HEIGHT	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)
THROWING DISTANCE	3 - 50 FT (.9 - 15.2 M)	3 - 50 FT (.9 - 15.2 M)	3 - 55 FT (.9 - 16.7 M)	3 - 50 FT (.9 - 15.2 M)	3 - 50 FT (.9-15.2 M)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°
CHUTE ROTATION	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC
SPEEDS	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM
LENGTH	58.6 IN (148.8 CM)	58.6 IN (148.8 CM)	58.6 IN (148.8 CM)	58.3 IN (148.1 CM)	58.3 IN (153.2 CM)
WIDTH	26.4 IN (67.1 CM)	29.9 IN (75.9 CM)	29.9 IN (75.9 CM)	32.4 IN (82.3 CM)	32.4 IN (76.7 CM)
HEIGHT	45.3 IN (115.1 CM)	45.3 IN (115.1 CM)	45.3 IN (115.1 CM)	45.5 IN (115.6 CM)	45.5 IN (118.4 CM)
WEIGHT	245.5 LBS (111.4 KG)	249.8 LBS (113.3 KG)	267.5 LBS (121.3 KG)	275.6 LBS (125 KG)	275.6 LBS (125 KG)
ACCESSORIES AT A GLANCE	HANDWARMER KIT, TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TIRE CHAINS,TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER

Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0720